



Chen Hsong SM-TP Advanced Series Molding Machine:

The SM-TP Advanced Series Two Platen Servo Drive injection molding machine series is a revolutionary two-platen design. Designed by leading European and Japanese industry experts, it represents a unique combination of world-class, no compromise performance and characteristics. Numerous innovations protected by international patents give this machine a very good price-performance value. The SM-TP Advanced Series is the ultimate in reliability and flexibility at an unbelievable price!



Standard Features:

- Energy Saving Inovance Servo Pumps
- Powerful Beckhoff Controller
- 2 Core Pull Circuits, 2 Air Blow Circuits
- High Torque Screw Drive
- Eject on the Fly
- Multiple Ejector Control
- Precise Barrel and Nozzle Temperature Control
- Electrical, Mechanical and Hydraulic Safeties
- Water Flow Meters
- Spare Parts Kit— Heaters Bands, Leveling Pads, Filters and Mold Clamps
- CE Declaration
- Euomap Standards
- E67 Robot Interface
- 2-Year Limited Factory Warranty—Parts & Labor!
- 3-Year Limited Warranty on Frames & Castings

Available Options:

- Special Screw and Barrel Designs— High Mixing, Rigid PVC, PET, PMMA, Reinforced Nylon & more
- Injection units listed are standard, shot size from 69.4 to 3,742 ounces available
- Additional Core Pull and Air Blast Circuits
- Electric Screw Drive and Shut Off Nozzle
- Integrated Valve Gate & Hot Runner Controls
- High Heat Packages
- Apex 3-Axis Servo Robots (5-Axis Units available as well for 3-plate molds)



Technology Creates the Future
60 Years of Focus, Determined to Continue Innovating

SM 1250 TP Advanced Series

CLAMPING UNIT	Inches	mm	
Clamping Force (US-Tons)	1378		
Opening Stroke	59.05-90.55	1500-2300	
Platen Size	76.77x74.8	1950x1900	
Space Between Tie Bars	54.33x50.39	1380x1280	
Min-Max Mold Height	19.68-51.18	500-1300	
Max daylight	110.23	2800	
Mold Register Hole	9.84	250	
Ejector Force (US-Tons)	15.74	15.74	
Stroke	400	608	
STANDARD INJECTION UNIT		P1	P2
Screw Diameter	Inches	4.33	4.72
	mm	110	120
Screw L/D ratio	L/D	22	20.2
Shot volume	In ³	318.78	379.38
Shot size (PS)	Ounces	167.69	199.58
	Grams	4754	5658
Inj. Pressure (max)	PSI	26686	22480
Inj. Rate	In ³ /sec	50.34	59.92
Screw Stroke	Inches	21.65	
	mm	550	
Screw Rotation Speed (max)	RPM	115	
Nozzle Forward Force (max)	US-Tons	16.53	

POWER		
System Pressure	PSI	2538
Motor Power	KW (HP)	104.5 (142)
Electric Heating Power	KW	50
Temperature Control Zones		7+1

OTHER INFORMATION WITH STANDARD INJECTION UNIT		
Oil tank Capacity	Gallon	608
Machine Weight (Approx.)	Lbs	121254
Machine Dimensions (L*W*H)	Inches	441x138x118
	mm	11.2x3.5x3
Standard Injection Unit		P

***additional injection units with larger & smaller shot sizes available.