



Chen Hsong SM-TP Advanced Series Molding Machine:

The SM-TP Advanced Series Two Platen Servo Drive injection molding machine series is a revolutionary two-platen design. Designed by leading European and Japanese industry experts, it represents a unique combination of world-class, no compromise performance and characteristics. Numerous innovations protected by international patents give this machine a very good price-performance value. The SM-TP Advanced Series is the ultimate in reliability and flexibility at an unbelievable price!



Standard Features:

- Energy Saving Inovance Servo Pumps
- Powerful Beckhoff Controller
- 2 Core Pull Circuits, 2 Air Blow Circuits
- High Torque Screw Drive
- Eject on the Fly
- Multiple Ejector Control
- Precise Barrel and Nozzle Temperature Control
- Electrical, Mechanical and Hydraulic Safeties
- Water Flow Meters
- Spare Parts Kit— Heaters Bands, Leveling Pads, Filters and Mold Clamps
- CE Declaration
- Euomap Standards
- E67 Robot Interface
- 2-Year Limited Factory Warranty—Parts & Labor!
- 3-Year Limited Warranty on Frames & Castings

Available Options:

- Special Screw and Barrel Designs— High Mixing, Rigid PVC, PET, PMMA, Reinforced Nylon & more
- Injection units listed are standard, shot size from 69.4 to 3,742 ounces available
- Additional Core Pull and Air Blast Circuits
- Electric Screw Drive and Shut Off Nozzle
- Integrated Valve Gate & Hot Runner Controls
- High Heat Packages
- Apex 3-Axis Servo Robots (5-Axis Units available as well for 3-plate molds)



Technology Creates the Future
60 Years of Focus, Determined to Continue Innovating

SM 1900 TP Advanced Series

CLAMPING UNIT	Inches	mm	
Clamping Force (US-Tons)	2094.4		
Opening Stroke	66.92-98.42	1700-2500	
Platen Size	90.55x88.97	2300x2260	
Space Between Tie Bars	65.74x61.02	1670x1550	
Min-Max Mold Height	27.55-59.05	700-1500	
Max daylight	125.98	3200	
Mold Register Hole	12.4	315	
Ejector Force (US-Tons)	17.71	17.71	
Stroke	450	912	
STANDARD INJECTION UNIT		R1	R2
Screw Diameter	Inches	5.51	5.9
	mm	140	150
Screw L/D ratio	L/D	22	20.5
Shot volume	In ³	657.2	754.49
Shot size (PS)	Ounces	345.72	396.86
	Grams	9801	11251
Inj. Pressure (max)	PSI	26106	22770
Inj. Rate	In ³ /sec	79.08	90.8
Screw Stroke	Inches	27.56	
	mm	700	
Screw Rotation Speed (max)	RPM	95	
Nozzle Forward Force (max)	US-Tons	16.53	

POWER		
System Pressure	PSI	2538
Motor Power	KW (HP)	159.5 (216.9)
Electric Heating Power	KW	95
Temperature Control Zones		7+1

OTHER INFORMATION WITH STANDARD INJECTION UNIT		
Oil tank Capacity	Gallon	912
Machine Weight (Approx.)	Lbs	180779
Machine Dimensions (L*W*H)	Inches	508x166x138
	mm	12.9x4.2x3.5
Standard Injection Unit		R

***additional injection units with larger & smaller shot sizes available.