



**Chen Hsong SM-TP Advanced Series Molding Machine:**

The SM-TP Advanced Series Two Platen Servo Drive injection molding machine series is a revolutionary two-platen design. Designed by leading European and Japanese industry experts, it represents a unique combination of world-class, no compromise performance and characteristics. Numerous innovations protected by international patents give this machine a very good price-performance value. The SM-TP Advanced Series is the ultimate in reliability and flexibility at an unbelievable price!



**Standard Features:**

- Energy Saving Inovance Servo Pumps
- Powerful Beckhoff Controller
- 2 Core Pull Circuits, 2 Air Blow Circuits
- High Torque Screw Drive
- Eject on the Fly
- Multiple Ejector Control
- Precise Barrel and Nozzle Temperature Control
- Electrical, Mechanical and Hydraulic Safeties
- Water Flow Meters
- Spare Parts Kit— Heaters Bands, Leveling Pads, Filters and Mold Clamps
- CE Declaration
- Euomap Standards
- E67 Robot Interface
- 2-Year Limited Factory Warranty—Parts & Labor!
- 3-Year Limited Warranty on Frames & Castings

**Available Options:**

- Special Screw and Barrel Designs— High Mixing, Rigid PVC, PET, PMMA, Reinforced Nylon & more
- Injection units listed are standard, shot size from 69.4 to 3,742 ounces available
- Additional Core Pull and Air Blast Circuits
- Electric Screw Drive and Shut Off Nozzle
- Integrated Valve Gate & Hot Runner Controls
- High Heat Packages
- Apex 3-Axis Servo Robots (5-Axis Units available as well for 3-plate molds)



Technology Creates the Future  
60 Years of Focus, Determined to Continue Innovating

***SM 2600 TP Advanced Series***

CLAMPING UNIT	Inches	mm	
Clamping Force (US-Tons)	2866		
Opening Stroke	74.80-102.36	1900-2800	
Platen Size	106.29x102.36	2700x2600	
Space Between Tie Bars	75.98x68.11	1930x1730	
Min-Max Mold Height	31.49-66.92	800-1700	
Max daylight	149.6	3600	
Mold Register Hole	12.4	315	
Ejector Force (US-Tons)	19.68	19.68	
Stroke	500	1070	
STANDARD INJECTION UNIT		B1	B2
Screw Diameter	Inches	5.9	6.88
	mm	150	175
Screw L/D ratio	L/D	22	18.9
Shot volume	In <sup>3</sup>	883.8	1202.96
Shot size (PS)	Ounces	464.91	632.78
	Grams	13180	17939
Inj. Pressure (max)	PSI	26106	19144
Inj. Rate	In <sup>3</sup> /sec	79.08	107.64
Screw Stroke	Inches	32.28	
	mm	820	
Screw Rotation Speed (max)	RPM	95	
Nozzle Forward Force (max)	US-Tons	16.53	

POWER		
System Pressure	PSI	2538
Motor Power	KW (HP)	159.5 (216.9)
Electric Heating Power	KW	100
Temperature Control Zones		7+1

OTHER INFORMATION WITH STANDARD INJECTION UNIT		
Oil tank Capacity	Gallon	1070
Machine Weight (Approx.)	Lbs	242508
Machine Dimensions (L*W*H)	Inches	535x174x146
	mm	13.6x4.4x3.7
Standard Injection Unit		B

\*\*\*additional injection units with larger & smaller shot sizes available.